

SM Transparency Catalog ► TOTO ► EcoPower® Toilet Flush Valve



Download PDF

TOTO_®

EcoPower Toilet Flush Valve

TET1UA - 1.0 gpf



Performance Dashboard



1.0 gpf EcoPower® Ultra High-Efficiency Toilet (HET) electronic flushometer valve

Hydropower self-generating system

Automatic sensor activated

24 hour automatic flush for trap seal protection

Piston valve technology

Manual override button

ADA compliant

Visit TOTO for more product specifications:

TET1UA

See ecomedes for water & energy calculations

CSI MasterFormat™ #22 42 43

Check specs sheet for this product For spec help call (888) 295-8134

Powered by water to create an electrical current

· Reduces electricity use, lower maintenance costs and hands-free, automatic-shut-off functionality

Environmental performance

Improved by:

Powered by the sheer force of running water

Saves 38% and 22% more water than standard 1.6gpf and 1.28gpf valves

Metal parts and electric components are recyclable at the end of service

Certifications, rating systems & disclosures:


Contributes to earning credits in LEED®

CALGreen® compliant

Declare™ Label, LBC Compliant

See LCA results & interpretation

See material health results & interpretation











SM Transparency Report™+ Material Health Overview™

VERIFICATION LCA ✓ NSF 3rd party reviewed Transparency Report **NSE Verified** Material Health Evaluation

Validity: 10/16/2017 - 10/16/2022 TOT - 10/16/2017 - 027

Self-declared

The LCA and Report are independently reviewed and verified to the SM Transparency Report Framework and ISO 14025.

NSF International

P.O Box 130140 789 N.Dixboro Road Ann Arbor, MI 48105, USA

+1 734 769 8010



The material health evaluation is self-declared and done in accordance with the Manufacturers **Guide to Declare.**

International Living Future Institute

501 East Madison St. Seattle, WA 98122 www.living-future.org 206 223 2028



TOTO USA

1155 Southern Road Morrow, GA 30260

Contact us

EcoPower® Toilet Flush Valve TET1UA

LCA results & interpretation

Life cycle assessment

Scope and summary

○ Cradle to gate ○ Cradle to gate with options **②** Cradle to grave

Reference service life: 10 years. One flush valve for toilets in an average

Functional unit

U.S. commercial environment for 10 years. The period of 10 years is modeled as the period of application based on the average technical lifespan for commercial applications. The economical lifespan of commercial applications can be longer or shorter due to aesthetic replacements or more intense use. The implication is that the LCA model assumes that the application ends at year 10 and that the materials will be treated in an endof-life scenario.

Data reporting period: 2016


Default use phase scenario 10 years of service in an average U.S. commercial environment in

combination with a toilet with 1.0 gallon/use, 51 uses/day, and 260 days/year resulting in 132,600 gallons of water.

MATERIAL

Material composition greater than 1% by weight

Valve body	Bronze (C83600)	32.0%
Bottom cover	Zinc die cast	16.0%
Top cover	Zinc die cast	14.4%
Packaging	Cardboard	13.8%
Valve cap	Bronze (C83600)	7.2%
Valve tailpiece	Bronze (C83600)	3.2%
Tailpiece nut	Brass	1.2%
Manuals	Paper	1.1%
Generator coil	Copper	1.0%
	Other	10.0%



All life cycle stages

What's causing the greatest impacts

The use and production stages are both important and dominate the results for all impact categories. The impact of the use stage is mostly due to the embedded energy arising from acquisition, treatment and distribution of the water used during the use of the toilet for which the valves are installed. The production stage itself has a significant contribution to eutrophication (mostly from emissions from copper mining), non-carcinogens (emissions from the production of coal, copper and zinc) and ecotoxicity (mostly from the disposal of steel slags and bottom ashes, as well as from barium emissions to water due to the extraction processes of natural gas).

preventing the need to produce primary materials. Recycling is a relevant factor for some of the impact categories, offsetting a portion of the impacts caused by production. Additionally, the delivery of the product to the construction/installation site, the construction/installation processes, the processes for dismantling the product and final waste treatment during the end of life stage do not have a significant impact. **Production stage**

Bronze and zinc parts, together with the printed wiring board, have

The recovery stage includes recycling processes and benefits by

the LCA results.

AVG. % WT.

significant contributions to the impact categories. The stainless steel material is relevant to the carcinogenics category. The electroplating process is a major contributor to the ozone depletion category while the die casting process is relevant to the ecotoxicity and non-carcinogenics categories. Additionally, polishing and potting have a somewhat significant processing contribution to the results. Transport via oceanic freighter appears as a relevant contributor to the fossil fuel depletion and smog categories. The remaining parts and processes contribute between 3% and 15% to the overall impacts in the rest of the categories. Sensitivity analysis

TOTO PeoplePlanetWater... programs improving environmental performance

There are no sensitivity results that lead to variations greater than 10% in

TOTO's EcoPower® products are powered by the force of running

- water. The electronic and mechanical components are programmed and
- designed to allow water flow and accurate flush volume only when needed. Water consumption is reduced in the use phase due to superior flushing performance.
- See how we make it greener

32.38 mPts

0.02 mPts

END OF LIFE

-1.50 mPts

RECOVERY

-1.83E+01

1/2 product

1 product

2 points

LCA results

LIFE CYCLE STAGE	PRODUCTION	CONSTRUCTION	USE	END OF LIFE	RECOVERY
Information modules: Included Excluded	A1 Raw Materials	A4 Transportation/ Delivery	B1 Use	C1 Deconstruction/ Demolition	D Reuse, recovery and/or recycling
*Installation and deconstruction/demolition are mostly manual. The sanitary fittings should not need repair, maintenance or	A2 Transportation	A5 Construction/ Installation	B2 Maintenance	C2 Transportation	
replacement during the modeled life time.	A3 Manufacturing		B3 Repair	C3 Waste processing	
Reuse and energy recovery are not modeled for sanitary fittings.			B4 Replacement	C4 Disposal	
			B5 Refurbishment		
			B6 Operational energy use		
			B7 Operational water use		

Impacts per 10 years of service

31.81 mPts

Materials or processes contributing >20% to total impacts in each life cycle stage	Bronze and zinc parts together with the printed wiring board in addition to manufacturing processes such as die casting and electroplating.	Transportation of the product to the installation site or consumer and disposal of packaging.	Volume of water use during the operation of the product and the embedded energy use in the water used.	Transport to waste processing, waste processing and disposal of material flows transported to a landfill.	Plastic and metal components' recycling processes.			
TRACI v2.1 results per one flush valve								

0.14 mPts

PRODUCTION

Ecological damag	ge						
Impact Category	Unit						
Acidification	kg SO₂ eq	?	1.65E+00	1.46E-02	2.34E+00	2.17E-03	-8.72E-02
Eutrophication	kg N eq	?	1.10E+00	1.45E-03	2.57E-01	2.28E-04	-2.09E-02
Global warming	kg CO₂ eq	3	8.72E+01	1.63E+00	4.49E+02	2.70E-01	-5.50E+00
Ozone depletion	kg CFC-11 eq	?	6.34E-06	3.59E-09	2.03E-05	3.22E-08	-3.89E-07
Human health da	ımage						
Impact Category							
	Unit						
Carcinogenics	Unit CTU _h	3	2.45E-06	1.83E-08	9.22E-06	2.52E-09	-1.75E-07
Carcinogenics Non-carcinogenics		?	2.45E-06 2.87E-04	1.83E-08 1.71E-07	9.22E-06 3.80E-05	2.52E-09 1.78E-08	-1.75E-07 -1.27E-05
-	CTU _h						

Impact Category Unit 4.73E+02 **Ecotoxicity CTU**_e

Additional environmental information

3.23E+00

TOTO Sanitary Fittings Products LCA Background Report (public version), September 2017

References

SM Transparency Report Framework Part A: LCA Calculation Rules and Background Report Requirements v2017

LCA Background Report

(compliant with ISO14040-44 and ISO14025) Part B: Product Group Definition – Commercial Flushometer Valves

Transparency Reports™ / environmental product declarations enable purchasers and users to compare the potential environmental performance of products on a life cycle basis. They are designed to present information transparently to make the limitations of comparability more

comparisons. They therefore, cannot be used as comparative assertions unless the conditions defined in ISO 14025 Section 6.7.2. 'Requirements for Comparability' are satisfied.

understandable. TRs/EPDs of products that conform to the same PCR and include the same life

cycle stages, but are made by different manufacturers, may not sufficiently align to support direct

who have verified improved life-cycle environmental performance. LEED BD+C: New Construction | v4 - LEED v4 Building product disclosure and optimization

The intent is to reward project teams for selecting products from manufacturers

2.18E-01

Industry-wide (generic) EPD

Green Globes for New Construction and Sustainable Interiors

Environmental product declarations

✓ Product-specific Type III EPD

Third-party certified type III EPD

Materials and resources

1.55E+02

Rating systems

NC 3.5.1.2 Path B: Prescriptive Path for Building Core and Shell

Collaborative for High Performance Schools National Criteria **Materials and resources**

C 3.5.2.2 and SI 4.1.2 Path B: Prescriptive Path for Interior Fit-outs

3rd party reviewed

VERIFICATION LCA The LCA and Report are The material health evaluation is independently reviewed and verified self-declared and done in **✓** NSF.

SM Transparency Report™+ Material Health Overview™

Transparency Report **✓** NSE Verified Material Health Evaluation Self-declared

Validity: 10/16/2017 - 10/16/2022

TOT - 10/16/2017 - 027

to the SM Transparency Report Framework and ISO 14025. **NSF** International

P.O Box 130140 789 N.Dixboro Road Ann Arbor, MI 48105, USA +1 734 769 8010

accordance with the Manufacturers **Guide to Declare. International Living Future**

Institute 501 East Madison St. Seattle, WA 98122

206 223 2028



TOTO USA 1155 Southern Road

Contact us

Morrow, GA 30260

SM Transparency Catalog ► TOTO ► EcoPower® Toilet Flush Valve



Download PDF

LCA & material health results & interpretation

EcoPower® Toilet Flush Valve TET1UA

Material health

Evaluation program: Declare

Declare labels are issued to products disclosing ingredient inventory, sourcing and end of life options. Declare labels are based on the Manufacturers Guide to Declare, administered by the International Living Future Institute (ILFI).

How it works

Material ingredients are inventoried and screened against the Living Building Challenge (LBC) Red List which represents the 'worst in class' materials, chemicals, and elements known to pose serious risks to human health and the greater ecosystem.

The Declare product database and label are then used to select products that meet the Living Building Challenge's stringent materials requirements, streamlining the materials specification and certification process.

Assessment scope and results

Inventory threshold: 100 ppm

Declaration status:

The Declare product database and label are used to select products that meet the LBC's stringent materials requirements, streamlining the materials specification and certification process.

LBC Red List Free ? LBC Compliant ? Declared ?

Click the label to see the full declaration.

EcoPower® 1.0 gpf Toilet Flush Valve **TET1UA**



How this rating was achieved

Declare level

'Living Building Challenge Compliant' is achieved when the product contains Red List ingredients that have been given a temporary exception by the Living Building Challenge due to current market limitations.

What's in the product and why

The flush valve cover is plated with chrome (Hexavalent Chromium VI). Chromium material is used as a decorative finish in applications where corrosion-resistance and durability are required. During the chrome plating process health hazards have been identified and are managed. Process controls are used to protect the environment and the production workers wear personal protection equipment. After the plating process the chrome surface is inert and does not pose any health risks. The cover in its final form does not represent any hazards to the user.

The TOTO facility in which the faucet is manufactured is ISO 14001 certified. This means that the facility has implemented an environmental management system as part of TOTO's commitment to the health of the environment.

Where it goes at the end of its life

TOTO encourages consumers to recycle their used used parts. Contact your local municipality for recycling programs.

How we're making it healthier

The EcoPower technology enables the flush valve to operate off the energy grid and requires no routine battery replacement. This technology helps to reduce pollution and hazardous waste, thereby mitigating human health impacts.

See how we make it greener

References

Declare

EcoPower® 1.0 gpf Toilet Flush Valve TET1UA

Manufacturer's Guide to Declare

A comprehensive guide providing information about the program, the assessment methodology, how to submit material data to obtain a Declare label and how they are used to meet the Health & Happiness and Materials Petals of the Living Building Challenge.

Rating systems

LEED BD+C: New Construction | v4 - LEED v4

Building product disclosure and optimization

Material ingredients

Credit value options

1 product each

✓ 1. Reporting
✓ 2. Optimization
✓ 3. Supply chain optimization

Living Building Challenge 3.0 **Materials petals imperatives**

10. Red List Free 12. Responsible Industry 13. Living Economy Sourcing

WELL Building Standard®

Air and Mind Features

Air 26. Enhanced Material Safety

Collaborative for High Performance Schools National Criteria MW 10.1 – Building Product Health Related Information Reporting

Mind 97. Material Transparency Mind 98. Organizational Transparency

Product Health Related Information Report

1 point

SM Transparency Report™+ Material Health Overview™

VERIFICATION

Self-declared

3rd party reviewed

LCA ✓ NSF

Transparency Report

✓ NSF Verified Material Health Evaluation

Validity: 10/16/2017 - 10/16/2022 TOT - 10/16/2017 - 027

The LCA and Report are independently reviewed and verified to the SM Transparency Report Framework and ISO 14025.

NSF International

P.O Box 130140 789 N.Dixboro Road Ann Arbor, MI 48105, USA www.nsf.org +1 734 769 8010



The material health evaluation is self-declared and done in accordance with the Manufacturers Guide to Declare.

International Living Future Institute 501 East Madison St.

Seattle, WA 98122 www.living-future.org 206 223 2028



TOTO USA 1155 Southern Road

Morrow, GA 30260

Contact us

SM Transparency Catalog ► TOTO ► EcoPower® Toilet Flush Valve

How we make it greener

EcoPower® Toilet Flush Valve TET1UA

Collapse all

See LCA results by life cycle stage










TOTO participates in the UPS Carbon Neutral program. TOTO is a certified SmartWay partner.

USE



TOTO's EcoPower® Toilet Flush Valves feature the highly regarded EcoPower technology. Engineered to reduce environmental impacts, TOTO's EcoPower products offer water and energy savings without sacrificing performance. Below are some of the features of TOTO's EcoPower technology.



SENSOR: Ensuring th


Ensuring that water flows only when needed, the self-adjusting EcoPower sensor eliminates "ghost" flushing that wastes water. A minimum of six seconds in front of the sensor is required to get its acknowledgement, and a three second flush delay after stepping away from the sensing zone prevents excessive flushing.

MICROTURBINE:

TOTO's EcoPower technology enables the product to operate 100% off grid. As water flows, the microturbine recharges capacitors for the sensor and solenoid. Less reliance on the back-up battery results in much less battery waste.

PISTON AND SOLENOID: The piston and solenoid med

The piston and solenoid mechanism, a marked improvement over traditional rubber diaphragm type valves, maintains consistent flush volume under a range of supply pressures.



Using the same proven engineering as our legendary EcoPower conventional and high-efficiency toilet flush valves, the ultra-high efficiency flush valve reinforces TOTO's performance reputation while offering an additional water savings of 20% and 38%, respectively.

END OF LIFE





Metal and electronic parts can be recycled at the end of life.



SM Transparency Report™+ Material Health Overview™



Material Health Evaluation

Self-declared

Validity: 10/16/2017 – 10/16/2022 TOT – 10/16/2017 – 027 The LCA and Report are independently reviewed and verified to the SM Transparency Report Framework and ISO 14025.

Framework and ISO 14025.

NSF International
P.O Box 130140
789 N.Dixboro Road

www.nsf.org +1 734 769 8010

Ann Arbor, MI 48105, USA

 $@2017 \mid The \ SM \ Transparency \ Report \\ ^{m}Program \ is \ operated \ by \ Sustainable \ Minds \\ @\mid Member, \ Program \ Operator \ Consortium \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ operator \ Consortium \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ \mid All \ rights \ reserved \ \mid Privacy \ policy \ polic$

The material health evaluation is self-declared and done in accordance with the Manufacturers Guide to Declare.

International Living Future Institute 501 East Madison St. Seattle, WA 98122 www.living-future.org 206 223 2028



1155 Southern Road Morrow, GA 30260 www.totousa.com

TOTO USA

Contact us